


## **CUSTOMER DATASHEET**


Printed: 08/11/2023


Product Management
Transportation Europe

Central Article Code: D23052C18-A Created: 28/10/2009

Local Code: EL605 Modified: 10/01/2023







Final Outlook C2318-A Approval date 15/01/2010

	_			$\overline{}$							_	_
_	_	ĸ	-		ı	w	IΑ	N	и	-51	_	•
	_			_			_	v v		_	_	•

Voltage (V): 12 V

C20 (Ah): 60.0 20 h Cranking (A): 520 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: Manufactured Specific

Endurance: Toyota Requirement (MHF)

## CONTAINER

Type: D23 BLACK Hold Down: B0

Hold Down: B0 H.D. Adapter: No

## COVER

Type: Flat/Screw Integrate BLACK

Polarity: ETN 1

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

## **STD. DIMENSIONS**

 Length (mm  $\pm$  2):
 230

 Width (mm  $\pm$  2):
 173

 Height (mm  $\pm$  2):
 222

 Total Weight (kg  $\pm$  5%):
 15.80

Type: 6 x M18 BLACK

**HANDLES** 

**PLUGS** 

Type: 1 x Integrated BLACK

**OTHERS** 

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.