


CUSTOMER DATASHEET


Printed: 08/11/2023


Product Management
Transportation Europe

Central Article Code: D26075C51-A Created: 16/06/2021

Local Code: EL754 Modified: 16/06/2021







Final Outlook D2651-A Approval date 15/06/2021

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	D26	BLACK
C20 (Ah):	75.0	20 h	Hold Down:	B0	
Cranking (A):	750	EN	H.D. Adapter:	No	
Charge:	WET		COVER		
Technology:	Vented/Flooded		Type:	Flat/Press integrated BLACK	
Grid:	Ca/Ca		Polarity:	ETN 0	
Vibration:	V1 (30Hz+/-2Hz/3g/2h) E2 (150c@50%) ref.EN-2015		Terminals:	EN taper post	
Endurance:			Terminal Adapter:	No	
			SOCI:	No	
			Ventilation:	Central	
STD. DIMENSIONS			Filter:	1 Filter at Right	
Length (mm ± 2):	270		Lateral Plug:	No	
Width (mm ± 2):	(mm ± 2): 173		PLUGS		
Height (mm ± 2):	222): 19.00		Type: 1 x VCL V	1 x VCL Vent BLACK	
Total Weight (kg ± 5%)			HANDLES		
			Type: 1 x Integra	ited	BLACK
			OTHERS		

All figures show nominal values. Tolerances are according to EN50342

and applicable European Regulations.

Degassing Tube:

No