


## **CUSTOMER DATASHEET**


Printed: 09/11/2023


Product Management
Transportation Europe

Central Article Code: D31065W22-A Created: 14/06/2010

Local Code: ER450 Modified: 31/07/2020







Final Outlook D3122-A Approval date 15/07/2010

PERFORMANCES		CONTAINER		
Voltage (V):	12 V	Type:	D31	BLACK
C20 (Ah):	95.0 20 h	Hold Down:	Korean B1	
Cranking (A):	650 EN	H.D. Adapter:	No	
Charge:	WET	COVER		
Technology:	Vented/Flooded	Type:	Flat/Press integrated BLUE LIGHT	
Grid:	Hybrid	Polarity:	ETN 1	
Vibration:	V2 (30Hz+/-2Hz/6g/2h)	Terminals:	EN taper post	
Endurance:	300 cycles@40%	Terminal Adapter:	No	
		SOCI:	Black SOCI with one ball	
		Ventilation:	Central	
STD. DIMENSIONS		Filter:	1 Filter at Right	
Length (mm ± 2):	306	Lateral Plug:	Lateral Plug: No	
Width (mm ± 2):	173	PLUGS		
Height (mm + 2)	222		: =000	

Width (mm ± 2): 173

Height (mm ± 2): 222

Total Weight (kg ± 5%): 21.70

Type: 1 x VCL Vent BLUE LIGHT

HANDLES

Type: 1 x Integrated BLACK

Type: 1 x Integrated BLACK

OTHERS

Degassing Tube: Elbow+Tube+Valve

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Tested acc. BCIS-08 Rev. Dec02