


CUSTOMER DATASHEET


Printed: 09/11/2023


Product Management Transportation Europe

D07076G02-A Created: 06/09/2005 Central Article Code:

ES1200 Modified: 20/03/2019 Local Code:







Final Outlook D0702-A Approval date 01/10/2005

PERFORMANCES

Voltage (V): 12 V

C20 (Ah): 110.0 20 h ΕN Cranking (A):

Charge: **CHARGED**

Technology: **GEL** Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: 200 cycles@100%

CONTAINER

D07 **BLACK** Type: Hold Down: B0

H.D. Adapter: No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 2

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 286 Width $(mm \pm 2)$: 269 Height (mm ± 2): 230 Total Weight (kg ± 5%): 37.50

6 x M18 Valve

GREY MEDIUM Type:

HANDLES

PLUGS

2 x Rope (Rigid holder) BLACK Type:

OTHERS

Degassing Tube: No

Gel

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

DNV-GL type approved 2015