


## **CUSTOMER DATASHEET**


Printed: 09/11/2023


Product Management
Transportation Europe

Central Article Code: D02046G12-A Created: 05/09/2005

Local Code: ES950 Modified: 20/07/2023







Final Outlook D0212-A Approval date 01/10/2005

	D		$\frown$	D	N/	ΙΑ	NI			c
 ▝⊏	К	г,	u	К	IV	м	IV	u	⊏,	o

Voltage (V): 12 V

C20 (Ah): 85.0 20 h Cranking (A): 0 EN

Charge: CHARGED

Technology: GEL Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: 300 cycles@100%

CONTAINER

D02

Hold Down: B0
H.D. Adapter: No

Type:

COVER

**BLACK** 

Type: Flat/Screw BLACK

Polarity: ETN 1

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

## **STD. DIMENSIONS**

 Length (mm  $\pm$  2):
 349

 Width (mm  $\pm$  2):
 175

 Height (mm  $\pm$  2):
 235

 Total Weight (kg  $\pm$  5%):
 28.20

Type: 6 x M18 Valve

GREY MEDIUM

HANDLES

Type: 2 x Rigid BLACK

OTHERS

**PLUGS** 

Degassing Tube: No

DNV-GL type approved 2015/Used for Bosch

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.